

Kozane[®] Cut-Resistant Chaps

Art. no. 708-05

Designed to offer the highest level of cut resistance on the legs, with adjustable straps. Suitable for work environments where there is a risk of cuts and lacerations to the front of the legs. Manufactured using our Kozane[®] Extreme cut-resistant fabric (article number 500.3100).



| | |
|---|----------------------------|
| EN 388:2016 6.1 Abrasion | Level 3 |
| EN 388:2016 6.2 Blade cut resistance | Level X* |
| EN 388:2016 6.4 Tear resistance | Level 4 |
| EN 388:2016 6.5 Puncture resistance | Level 4 |
| EN 388:2016 6.3 Cut resistance method (EN ISO 13997:1999) | Level F |
| ANSI ASTM F2992-15 | Cut A8 (Cut Score: 5,215g) |

*x stands for not tested. As per clause 6.2.6 of EN 388:2016 for materials dulling the blades, if after the first sequence the number of cycles Cn+1 is greater than 3 times Cn in one of the tested specimen, the EN ISO 13997:1999 Cut resistance method as per clause 6.3 shall be performed and this method becomes the reference test method for the assessment of the protection against cut risks.

PATENT PENDING

Applications:

- Glass handling
- Transportation and manufacturing
- Paper/pulp processing
- General manufacturing

| | |
|------------------------------|----------------------|
| Size | One Size, Adjustable |
| Colour | Black |
| Safety and care instructions | |